

K

This product is compatible to B1219645 TYPE 28 FOR USE IN
DO NOT EXPOSE TO:

- DIRECT SUNLIGHT.
- HIGH HUMIDITY OR HIGH TEMPERATURES

DO NOT STORE OVER :

- 40 DEGREES CELCIUS (40°C) 104 DEGREES FAHRENHEIT

Replace all the BLACK developer, This compatible developer can be used with new machines or with existing machines.

This Packaging contains Ceramic Materials, Polyester resin, Silicone resin, Carbon black. Proportion confidential. Manufactured in Japan, Packed and mixed in The Netherlands. Lupine Trading Group BV is a trading and manufacturing company, based in The Netherlands. We only sell to Wholesale channels never to end users. This Compatible product can only be placed by specialised engineers.

Registered Trademarks or trade styles are the sole property of their respective owners and are used for descriptive purposes only. This Package contains Plastic, Metal Aluminium, Paper, Other This product is not sourced from or endorsed by Ricoh® Corporation. It's a Compatible product!
Net Weight 345GRM



K

This product is compatible to B1219645 TYPE 28 FOR USE IN
DO NOT EXPOSE TO:

- DIRECT SUNLIGHT.
- HIGH HUMIDITY OR HIGH TEMPERATURES

DO NOT STORE OVER :

- 40 DEGREES CELCIUS (40°C) 104 DEGREES FAHRENHEIT

Replace all the BLACK developer, This compatible developer can be used with new machines or with existing machines.

This Packaging contains Ceramic Materials, Polyester resin, Silicone resin, Carbon black. Proportion confidential. Manufactured in Japan, Packed and mixed in The Netherlands. Lupine Trading Group BV is a trading and manufacturing company, based in The Netherlands. We only sell to Wholesale channels never to end users. This Compatible product can only be placed by specialised engineers.

Registered Trademarks or trade styles are the sole property of their respective owners and are used for descriptive purposes only. This Package contains Plastic, Metal Aluminium, Paper, Other This product is not sourced from or endorsed by Ricoh® Corporation. It's a Compatible product!
Net Weight 345GRM



K

This product is compatible to B1219645 TYPE 28 FOR USE IN
DO NOT EXPOSE TO:

- DIRECT SUNLIGHT.
- HIGH HUMIDITY OR HIGH TEMPERATURES

DO NOT STORE OVER :

- 40 DEGREES CELCIUS (40°C) 104 DEGREES FAHRENHEIT

Replace all the BLACK developer, This compatible developer can be used with new machines or with existing machines.

This Packaging contains Ceramic Materials, Polyester resin, Silicone resin, Carbon black. Proportion confidential. Manufactured in Japan, Packed and mixed in The Netherlands. Lupine Trading Group BV is a trading and manufacturing company, based in The Netherlands. We only sell to Wholesale channels never to end users. This Compatible product can only be placed by specialised engineers.

Registered Trademarks or trade styles are the sole property of their respective owners and are used for descriptive purposes only. This Package contains Plastic, Metal Aluminium, Paper, Other This product is not sourced from or endorsed by Ricoh® Corporation. It's a Compatible product!
Net Weight 345GRM



K

This product is compatible to B1219645 TYPE 28 FOR USE IN
DO NOT EXPOSE TO:

- DIRECT SUNLIGHT.
- HIGH HUMIDITY OR HIGH TEMPERATURES

DO NOT STORE OVER :

- 40 DEGREES CELCIUS (40°C) 104 DEGREES FAHRENHEIT

Replace all the BLACK developer, This compatible developer can be used with new machines or with existing machines.

This Packaging contains Ceramic Materials, Polyester resin, Silicone resin, Carbon black. Proportion confidential. Manufactured in Japan, Packed and mixed in The Netherlands. Lupine Trading Group BV is a trading and manufacturing company, based in The Netherlands. We only sell to Wholesale channels never to end users. This Compatible product can only be placed by specialised engineers.

Registered Trademarks or trade styles are the sole property of their respective owners and are used for descriptive purposes only. This Package contains Plastic, Metal Aluminium, Paper, Other This product is not sourced from or endorsed by Ricoh® Corporation. It's a Compatible product!
Net Weight 345GRM

